

REMOVING ARMREST FOR TOYOTA CENTURY

To be ready, your gonna want a prying tool, Phillips screw driver and you want to lift your armrest up to move it out the way.

Now first what you want to do is locate this panel piece that's above your upper panel cover and pry it out. There are 3 clips that hold it in this order.

You most likely want to start to pry it out where I circled on this photo.



Here's what the clips look like in the back so you know where the openings to pry are.



Now once you remove this piece. You will now have to remove your console upper panel. This one is pretty weird taking off but hopefully it goes good. So there are 6 clips that I'll circle the

locations of them so you know where to watch out for



In the red are where the 6 clips are. Also watch out for the connectors on the right when prying. But I'd recommend to start prying where I circled in blue.

Once all clips are disengaged, you want to lift the bottom side of it, if pulled up properly, keep it lifted and pull it back to you and hopefully it will fully lift out, but there is a connector that has been clipped so don't force it once you pull it out.



The circled spot is the connector that's held down by a clip. Unplug that one first.



What i did for this since one of the blue connectors is hard to unplug is that I moved my driver seat all the way up, then unplugged the connectors i circled in red then layer to top of it flat on the seat for now.

Now that the console is out of the way, you'll see 2 screws that holds your console box in place. You want to unscrew them and put them something where you won't lose them.



This part where you remove the console box is kinda of tricky due to the shape of it as it has this type of hook shape that can't be seen until fully taken out. But what you want to do is try and lift the console box up from the front, though when doing that it'll stop moving as it gets stuck on the plastic piece that held the screws in for it. So you want to gently force it from under to go up. If done right ill come out with no issue



To fully take it out now, you want to angle it higher where it's pointing straight up, gently do this to insure something doesn't break on it.



You want to lift it up like that in the photo and gently pull and wiggle it out to remove the console box.

Finally, the 2 screws that hold the armrest down are fully exposed and can be unscrewed like usual. Once you unscrew them you are able to finally take out the armrest and replace it if needed.



Hoping this helps yall, and sorry if my wording is off. I really tried to explain it explain it as best as I could. But hoping this helps yall out. 👍